



# UL Online Certifications Directory

## JMLU2.MH25918

### Gaskets And Seals - Component

### Gaskets and Seals - Component

MH25918

Compound Dsg	Max Serv Temp	Min Serv Temp	Hardness Range	Tnsl Str	Elong	Max Comp Set	Max Tnsl Set	Use (1)
<b>Two part poured-in-place open cell Polyurethane supplied as two liquid components</b>								
Polytix 30.11 +	80C	-20C	—	25	100	—	—	(2)

(1) See explanation of end-use environments in guide for this category.

(2) Also suitable for use in UL 50 and UL 50E (continuous compression) applications.

Marking: Company name, compound designation and the UL Recognized Component Mark on material, on a substantial tag, on container or smallest packaging.

[Last Updated](#) on 2009-07-06

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

